


SIDE INWARD OPENING WINDOW FOR BOLTING, CIRCLE



model: W-IL(R)B-F-CI



Hinge configurations:

Detail B1
Single hinge for
 $\phi Di < \phi 700$

Detail B2
Double hinge for
 $\phi Di \geq \phi 700$



MATERIALS CONFIGURATION								
MAIN FRAME	MOVEABLE FRAME				GLASS RETAINING		SCREWS	
	1	2	3	4	2	4*	2	4*
1	X	X	X	X	X	X	X	X
2	X	X	X	X	X	X	X	X
3	X	X	X	X	X	X	X	X
4	X	X	X	X	X	X	X	X

Not available for the aluminum moveable frame

- Steel (acc. to PN-EN10025): S235JR; S355J2; A36; D36; E36
- St. steel (acc. to PN-EN10088): 1.4306 (304L); 1.4404 (316L); 1.4457 (316Ti)
- Alu. alloy (acc. to PN-EN755): EN-AW 5754; EN-AW 5083; EN-AW 6063; EN-AW 6060
- Brass (acc. to PN-EN12167): CuZn37




Available glass: single glass; laminated glass; tinted glass; heated glass; double glazed; triple glazed

Available single glass thicknesses: 6; 8; 10; 12; 15; 19; 25

Available accessories for windows: S; D; R; W; C - see accessories TDS

For fireproof unit see separate TDS

CUT-OUT
HOLE IN PLATE (HIP)



All dimensions are in mm

BOHAMET

marketing@bohамет.pl
design.office@bohамет.pl
www.bohamet.com